

5 4 3 2 1

REVISIONS				
LTR	DESCRIPTION	DATE	DWN	APVD
A	RELEASED	01Jan16	AW	WK

◆ 技术参数/Technical parameters

- 符合规范/Accord With Norm :EIA-364C
- 额定电流/Current Rating :1AMP
- 绝缘阻抗/Insulator Resistance :500MΩ Min.
- 接触阻抗/Contact Resistance :30mΩ Max.
- 耐电压值/Voltage Resistance :AC 250V
- 工作温度/Operating Temperature :-40℃ To +85℃
- 金属材料/Metallic Material :Phosphor Bronze
- 金属处理/Metal Treatment :Au 3u", Sn 120u"
- 绝缘材料/Insulator Material :LCP UL94V-0
- 耐焊接热/Resistance To Soldering Heat :275° C ±5° C 10S MAX

TOLERANCE: ±0.05
RECOMMENDED PCB LAYOUT
(TOP VIEW)

剖面 A-A
比例 1: 1

装配合高

50.20	52.20	50.75	49.00	2X50P	BTB100-250-001
32.20	34.20	32.75	31.00	2X32P	BTB100-232-001
DIM D	DIM C	DIM B	DIM A	PIN NO.	PART NUMBER (料号)

THIS DRAWING IS A CONTROLLED DOCUMENT.

DIMENSIONS:
mm

THIRD ANGLE PROJECTION

TOLERANCES UNLESS OTHERWISE SPECIFIED:

0 PLC	± 0.50
1 PLC	± 0.30
2 PLC	± 0.20
3 PLC	± 0.15
4 PLC	± -
ANGLES	± 3°

DWN	01Jan2016
A. WU	
CHEK	01Jan2016
S. CHIEN	
APVD	01Jan2016
Abel	
PRODUCT SPEC	
WEIGHT	

东莞市宇亮电子有限公司
DONG GUAN YU LIANG ELECTRONICS CO., LTD

NAME
1.0 mm 间距 板对板 插头 H=10.3
2xNpin, VERTICAL, SMT.

SIZE
A4

DRAWING No. (图号)
YL-ED-01436

CUSTOMER DRAWING

SCALE 1 : 1 SHEET 1 of 1

科技 . 链接 . 未来

TEL:0769-83710858 FAX:0769-83710918 Http://www.dgyuliang.com