

5 4 3 2 1

◆ 技术参数/Technical parameters

- 符合规范/Accord With Norm :EIA-364C
- 额定电流/Current Rating :5AMP
- 绝缘阻抗/Insulator Resistance :1000MΩ Min.
- 接触阻抗/Contact Resistance :20mΩ Max.
- 耐电压值/Voltage Resistance :AC 500V
- 工作温度/Operating Temperature :-40°C To +105°C
- 金属材料/Metallic Material :Brass
- 金属处理/Metal Treatment :Ni50u" + Au2u" + Sn120u"
- 绝缘材料/Insulator Material :PA6T+30%GF UL94V-0
- 耐焊接热/Resistance To Soldering Heat :260° C ±5° C 10S MAX

TOLERANCE: ±0.05,  
RECOMMENDED PCB LAYOUT  
(TOP VIEW)

BTB254-218-XXX  
PART NUMBER  
(料号)

A	RELEASED	2017\04\07	AW	WK
LTR (版本)	DESCRIPTION (变更内容描述)	DATE (日期)	DWN (绘图)	APVD (核准)
REVISIONS (修订)				

THIS DRAWING IS A CONTROLLED DOCUMENT.  
(此图为宇亮公司受控文件)

DIMENSIONS: (单位) mm	TOLERANCES UNLESS OTHERWISE SPECIFIED: (自由公差参照)
<p>THIRD ANGLE PROJECTION (第三视角)</p>	0 PLC ± 0.50
	1 PLC ± 0.30
	2 PLC ± 0.20
	3 PLC ± 0.15
	4 PLC ± -
	ANGLES (角度公差)
	± 3°

DWN (绘图) A. WU	2017\04\07	<b>东莞市宇亮电子有限公司</b> DONG GUAN YU LIANG ELECTRONICS CO., LTD
CHEK (审核) S. CHIEN	2017\04\07	
APVD (核准) Abel	2017\04\07	
PRODUCT SPEC (产品规范)		
NAME (品名)	2.54 MM PITCH BOARD TO BOARD, 36P FEMALE.	
SIZE (尺寸)	A4	DRAWING No. (图号)
WEIGHT (产品重量)		YL-ED-XXXXX
CUSTOMER DRAWING (业务图)	SCALE (比例)	1 : 1
	SHEET (页码)	1 OF 1

TEL:0769-83710858 FAX:0769-83710918 Http://www.dgyuliang.com