

PH254-2XX-XXX

Pin Header
 Pitch 2.54mm
 2: Dual Row


Type1/Type2

 No.of Pins
 Dual Row:4~80

DIM A	DIM B
3.00	15.26
.....

产品规范 PRODUCT SPECIFICATION

1. 绝缘材质 INSULATOR MATERIAL : POLYESTER, UL94V-0 .
2. 端子材质 TERMINAL MATERIAL : COPPER ALLOY .
3. 端子电镀 FINISH : GOLD OR TIN PLATED.
4. 额定电流 CURRENT RATING : 3 AMPERE.
5. 绝缘阻抗 INSULATION RESISTANCE : 1000M OHMS MIN.
6. 耐电压 DIELECTRIC WITHSTANDING VOLTAGE : 1000 V /1 MINUTE.
7. 接触阻抗 CONTACT RESISTANCE : 初期 Initial : 20 m Ohm Max. ;
测试后 Final : 40 m Ohm Max. .
8. 操作温度范围 OPERATING TEMPERATURE : - 40°C to +105°C.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	08Jan2016	东莞市宇亮电子有限公司 DONG GUAN YU LIANG ELECTRONICS CO.,LTD		
 THIRD ANGLE PROJECTION		CHEK	08Jan2016			NAME Pin Header 2.54mm Dual Row DIP Type
		APVD Abel	08Jan2016	SIZE A4		
		TOLERANCES UNLESS OTHERWISE SPECIFIED:		PRODUCT SPEC	DRAWING No. YL-ED-XXX	
		0 PLC ± 0.50 1 PLC ± 0.30 2 PLC ± 0.20 3 PLC ± 0.15 4 PLC ± - ANGLES ± 3°		WEIGHT	SCALE 1 : 1 SHEET 1 of 1	
		CUSTOMER DRAWING				